

# Technical data sheet

## R-600 T



### OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Coating	
Black	✓
Door opening	
Door opening left	✓
Door opening right	✓
Door opening on both sides	✓
AIR-System	
for room air independent installation	✓



# Technical data sheet

## R-600 T



### PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	120-125 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design 2015/1084/2015	✓
EN NORM	EN 13229
BImSchV	Stufe 2
Classe energetica di appartenenza	4 Stelle



# Technical data sheet

## R-600 T

200



### SERVICES

Thermal output	
Nominal heat output	7.9 kW
Fuelwood requirement	2.4 ≈ kg/h
Energy efficiency	79 %
Combustion air requirement	17.6 m <sup>3</sup> /h
Triple values	
Exhaust gas mass flow	5.9 g/s
Exhaust temperature	310 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O <sub>2</sub>	14 mg/Nm <sup>3</sup>
CO emission at 13 % O <sub>2</sub>	0.077 %
CO emission at 13 % O <sub>2</sub>	958 mg/Nm <sup>3</sup>
CO <sub>2</sub> concentration	11.8 %
OGC at 13 % O <sub>2</sub>	43 mg/Nm <sup>3</sup>
NO <sub>x</sub> at 13 % O <sub>2</sub>	77 mg/Nm <sup>3</sup>

### INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1000 mm

All information is provided without guarantee. Sketches are not true to scale.

22.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



# Technical data sheet

## R-600 T



### CONVECTION AIR

Convection air above	min. 300 cm <sup>2</sup>
Convection air below	min. 200 cm <sup>2</sup>

### Installation

