Technical data sheet
R-600 T

200

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Coating	
Black	✓
Door opening	
Door opening left	✓
Door opening right	✓
Door opening on both sides	✓
AIR-System	
for room air independent installation	✓



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

200

Technical data sheet
R-600 T

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	120-125 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13229
BImSchV	Stufe 2
Classe energetica di appartenenza	4 Stelle

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

attika
FEUERKULTUR

Technical data sheet
R-600 T

200

SERVICES

Thermal output	
Nominal heat output	7.9 kW
Fuelwood requirement	2.4 ≈ kg/h
Energy efficiency	79 %
Combustion air requirement	17.6 m^3/h
Triple values	
Exhaust gas mass flow	5.9 g/s
Exhaust temperature	310 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O2	14 mg/Nm^3
CO emission at 13 % O2	0.077 %
CO emission at 13 % O2	958 mg/Nm^3
CO2 concentration	11.8 %
OGC at 13 % O2	43 mg/Nm^3
NOx at 13 % O2	77 mg/Nm^3

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1000 mm

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

200


Technical data sheet
R-600 T

200

CONVECTION AIR

Convection air above	min. 300 cm^2
Convection air below	min. 200 cm^2

Installation



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

200