

Technical data sheet

VISIO 1

200



OPTIONS

| | |
|---------------------------------------|--------|
| Support frame | |
| Black, 6mm | ✓ |
| Stainless steel, 6mm | ✓ |
| Window frame | |
| Black | ✓ |
| Stainless steel | ✓ |
| Handles | |
| Oak wood handle dark stained | ✓ |
| Stainless steel | ✓ |
| Steel black | ✓ |
| AIR-System | |
| for room air independent installation | ✓ |
| Heat-storage module© | |
| Heat-storage module© | 154 kg |



200



Technical data sheet

VISIO 1



PRODUCT INFORMATION

| | |
|-------------------------------------|----------|
| Weight depending on model/equipment | |
| Weight depending on model/equipment | 154 kg |
| Ø Smoke outlet | |
| Ø Smoke outlet | 200 mm |
| Ø Air inlet | |
| Ø Air inlet | 150 mm |
| Certifications | |
| Energy efficiency class | A |
| Eco Design | ✓ |
| EN NC 6.4.23 | EN 13229 |
| BImSchV | Stufe 2 |
| Flamme Verte | ✓ |
| Classe energetica di appartenenza | 4 Stelle |



Technical data sheet

VISIO 1

200



SERVICES

| Thermal output | |
|---|-------------------------|
| Nominal heat output | 7 kW |
| Thermal output range min./max. | 5-9 kW |
| Fuelwood requirement | 2 ≈ kg/h |
| Energy efficiency | 80 % |
| Triple values | |
| Exhaust gas mass flow | 7.5 g/s |
| Exhaust temperature | 243 °C |
| Required delivery pressure | 12 Pa |
| Required delivery pressure at 0.8 times the nominal heat output | 10 Pa |
| Fire safety | |
| Dust at 13 % O ₂ | 5 mg/Nm ³ |
| CO emission at 13 % O ₂ | 0.09 % |
| CO emission at 13 % O ₂ | 1150 mg/Nm ³ |
| CO ₂ concentration | 8.9 % |
| OGC at 13 % O ₂ | 45 mg/Nm ³ |
| NO _x at 13 % O ₂ | 81 mg/Nm ³ |

INSTALLATION

| Furniture distance from the front glass | |
|--|---------|
| A: Furniture distance from the front glass | 1400 mm |

All information is provided without guarantee. Sketches are not true to scale.

24.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



Technical data sheet

VISIO 1



CONVECTION AIR

| | |
|----------------------|--------------------------|
| Convection air above | min. 600 cm ² |
| Convection air below | min. 400 cm ² |

Note

Maximum weight supported by the frame: 200 kg.

Installation

