

Technical data sheet

VISIO 100 F



OPTIONS

Designframe (non supporting)	
Black	✓
Stainless steel	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika fire app	Option
Home Automation	Option



Technical data sheet

VISIO 100 F



PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm 1/2" 3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	145 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
<div style="display: flex; align-items: center;"> <div style="border: 1px solid gray; padding: 2px;">Premias</div> <div style="margin-left: 10px;">×</div> </div>	✓
<div style="display: flex; align-items: center;"> <div style="border: 1px solid gray; padding: 2px;">M&G Group</div> <div style="margin-left: 5px; font-size: 8px;">6.4.23</div> </div>	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

WEB2PRINT.PRODUKTINFORMATIONENBIOETHANOL

Certifications	
SVGW	✓



Technical data sheet

VISIO 100 F

200



SERVICES

Output range	
Natural gas G20/20 mbar	1.1-8.3 kW
Propane gas G31/50 mbar	1.8-9 kW
Gas consumption	
Natural gas G20/20 mbar	1.1 m ³ /h
Propane gas G31/50 mbar	0.4 m ³ /h
Maximum load	
Natural gas G20/20 mbar	10.3 kW
Propane gas G31/50 mbar	11.2 kW
Energy efficiency	
Efficiency class Natural gas G20/20 mbar	1
Efficiency class Propane gas G31/50 mbar	1

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm

CONVECTION AIR

Convection air above	200 cm ²
Convection air below	200 cm ²

200



Technical data sheet

VISIO 100 F



Installation

