

# Technical data sheet

## VISIO 2 ELEMENT

### OPTIONS

|                                       |       |
|---------------------------------------|-------|
| Support frame                         |       |
| Black, 6mm                            | ✓     |
| Window frame                          |       |
| Black                                 | ✓     |
| Handles                               |       |
| Oak wood handle dark stained          | ✓     |
| Stainless steel                       | ✓     |
| Steel black                           | ✓     |
| Air-system                            |       |
| for room air independent installation | ✓     |
| Additional concrete element           |       |
| Additional concrete element           | 1 stk |



# Technical data sheet

## VISIO 2 ELEMENT

### PRODUCT INFORMATION

|                                     |          |
|-------------------------------------|----------|
| Weight depending on model/equipment |          |
| Weight depending on model/equipment | 649 kg   |
| Ø Smoke outlet                      |          |
| Ø Smoke outlet                      | 200 mm   |
| Ø Air inlet                         |          |
| Ø Air inlet                         | 150 mm   |
| Flue pipe outlet                    |          |
| Top                                 | ✓        |
| Rear                                | ✓        |
| Certifications                      |          |
| Energy efficiency class             | A        |
| Eco Design                          | ✓        |
| European standard                   | EN 16510 |
| BlmSchV                             | Stufe 2  |
| Flamme Verte                        | ✓        |
| Classe energetica di appartenenza   | 4 Stelle |

# Technical data sheet

## VISIO 2 ELEMENT

### SERVICES

| Thermal output                         |                          |
|----------------------------------------|--------------------------|
| Nominal heat output                    | 7.9 kW                   |
| Fuelwood requirement                   | 2.4 ≈ kg/h               |
| Energy efficiency                      | ≥75 %                    |
| Combustion air requirement             | 23.8 m <sup>3</sup> /h   |
| Triple values                          |                          |
| Exhaust gas mass flow                  | 7.9 g/s                  |
| Exhaust temperature                    | 299 °C                   |
| Minimum flue draught                   | -12 Pa                   |
| Fire safety                            |                          |
| Dust at 13 % O <sub>2</sub>            | ≤40 mg/Nm <sup>3</sup>   |
| CO emission at 13 % O <sub>2</sub>     | ≤0.12 %                  |
| CO emission at 13 % O <sub>2</sub>     | ≤1500 mg/Nm <sup>3</sup> |
| OGC at 13 % O <sub>2</sub>             | ≤120 mg/Nm <sup>3</sup>  |
| NO <sub>x</sub> at 13 % O <sub>2</sub> | ≤200 mg/Nm <sup>3</sup>  |

# Technical data sheet

## VISIO 2 ELEMENT

### Safety distances:

Information on safety distances can be found in the installation manual.

### Note:

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.