

# Technical data sheet

## VISIO 3:1 ST

200




### OPTIONS

|                                       |   |
|---------------------------------------|---|
| Support frame                         |   |
| Black, 6mm                            | ✓ |
| Stainless steel, 6mm                  | ✓ |
| Window frame                          |   |
| Black                                 | ✓ |
| Stainless steel                       | ✓ |
| Handles                               |   |
| Oak wood handle dark stained          | ✓ |
| Stainless steel                       | ✓ |
| Steel black                           | ✓ |
| AIR-System                            |   |
| for room air independent installation | ✓ |



200



# Technical data sheet

## VISIO 3:1 ST

200



### PRODUCT INFORMATION

|                                     |          |
|-------------------------------------|----------|
| Weight depending on model/equipment |          |
| Weight depending on model/equipment | 510 kg   |
| Ø Smoke outlet                      |          |
| Ø Smoke outlet                      | 200 mm   |
| Ø Air inlet                         |          |
| Ø Air inlet                         | 150 mm   |
| Certifications                      |          |
| Energy efficiency class             | A        |
| Eco Design                          | ✓        |
| EN Norm 6.4.23                      | EN 13229 |
| BImSchV                             | Stufe 2  |
| Flamme Verte                        | ✓        |
| Classe energetica di appartenenza   | 4 Stelle |

All information is provided without guarantee. Sketches are not true to scale.

27.04.2026 | 2 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



# Technical data sheet

## VISIO 3:1 ST



### SERVICES

| Thermal output  |                        |
|---|------------------------|
| Nominal heat output   | 10 kW                  |
| Thermal output range min./max.                                  | 8.7-10 kW              |
| Fuelwood requirement  | 2.9 ≈ kg/h             |
| Energy efficiency   | 80 %                   |
| Triple values   |                        |
| Exhaust gas mass flow   | 9.6 g/s                |
| Exhaust temperature   | 238 °C                 |
| Required delivery pressure                                      | 12 Pa                  |
| Required delivery pressure at 0.8 times the nominal heat output | 10 Pa                  |
| Fire safety   |                        |
| Dust at 13 % O <sub>2</sub>                                     | 18 mg/Nm <sup>3</sup>  |
| CO emission at 13 % O <sub>2</sub>                              | 0.0744 %               |
| CO emission at 13 % O <sub>2</sub>                              | 930 mg/Nm <sup>3</sup> |
| CO <sub>2</sub> concentration                                   | 8.8 %                  |
| OGC at 13 % O <sub>2</sub>                                      | 35 mg/Nm <sup>3</sup>  |
| NO <sub>x</sub> at 13 % O <sub>2</sub>                          | 87 mg/Nm <sup>3</sup>  |

### INSTALLATION

| Furniture distance from the front glass    |        |
|--|--------|
| A: Furniture distance from the front glass | 700 mm |
| Furniture distance from the side glass     |        |
| B: Furniture distance from the side glass  | 700 mm |

All information is provided without guarantee. Sketches are not true to scale.

27.04.2026 | 3 / 4



# Technical data sheet

## VISIO 3:1 ST



### Note

Maximum weight supported by the frame: 200 kg.

Please observe the national/regional regulations for floor protection.

### Sketches of safety distances

