

Technical data sheet

VISIO 70 T



OPTIONS

Designframe (non supporting)	
Black	✓
Stainless steel	✓
Anti-reflective glass	
Anti-reflective glass	✓
Operating	
Remote control	Standard
attika fire app	Option
Home Automation	Option



Technical data sheet

VISIO 70 T



PRODUCT INFORMATION

Connections	
Flue pipe Ø (LAS)	130/200 mm
Gas connection	Ø 12 mm 1/2" 3/8"
Weight depending on model/equipment	
Weight depending on model/equipment	125 - 150 kg
Permissible chimney systems	
Schiedel Ontop Metaloterm	✓
Jeremias	✓
M&G Group	✓
Poujoulat	✓
Certifications	
Energy efficiency class	A
CE	EU 2016/426
SVGW	19-015-3

WEB2PRINT.PRODUKTINFORMATIONENBIOETHANOL

Certifications	
SVGW	✓



Technical data sheet

VISIO 70 T

200



SERVICES

Output range	
Natural gas G20/20 mbar	1.1-6.5 kW
Propane gas G31/50 mbar	1.8-8.9 kW
Gas consumption	
Natural gas G20/20 mbar	0.9 m ³ /h
Propane gas G31/50 mbar	0.4 m ³ /h
Maximum load	
Natural gas G20/20 mbar	8.1 kW
Propane gas G31/50 mbar	11.2 kW
Energy efficiency	
Efficiency class Natural gas G20/20 mbar	1
Efficiency class Propane gas G31/50 mbar	1

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	500 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	500 mm

CONVECTION AIR

Convection air above	200 cm ²
Convection air below	200 cm ²

All information is provided without guarantee. Sketches are not true to scale.

22.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



Technical data sheet

VISIO 70 T



Installation

