

# Technical data sheet

## VISIO TUNNEL

200



### OPTIONS

Support frame	
Black, 6mm	✓
Stainless steel, 6mm	✓
Window frame	
Black	✓
Stainless steel	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
AIR-System	
for room air independent installation	✓



200



# Technical data sheet

## VISIO TUNNEL

200



### PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	235 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Eco Design	✓
EN Norm 6.4.23	EN 13229
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

One side has a lifting door, the other side is fixed. Both can be tilted for cleaning.

200



# Technical data sheet

## VISIO TUNNEL

200



### SERVICES

Thermal output	
Nominal heat output	8.6 kW
Thermal output range min./max.	7.5-8.6 kW
Fuelwood requirement	2.5 ≈ kg/h
Energy efficiency	80 %
Triple values	
Exhaust gas mass flow	7.7 g/s
Exhaust temperature	256 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O <sub>2</sub>	24 mg/Nm <sup>3</sup>
CO emission at 13 % O <sub>2</sub>	0.071 %
CO emission at 13 % O <sub>2</sub>	887 mg/Nm <sup>3</sup>
CO <sub>2</sub> concentration	9.3 %
OGC at 13 % O <sub>2</sub>	44 mg/Nm <sup>3</sup>
NO <sub>x</sub> at 13 % O <sub>2</sub>	99 mg/Nm <sup>3</sup>

### INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1200 mm

All information is provided without guarantee. Sketches are not true to scale.

21.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



# Technical data sheet

## VISIO TUNNEL



### CONVECTION AIR

Convection air above	min. 1050 cm <sup>2</sup>
Convection air below	min. 525 cm <sup>2</sup>

### Note

Maximum weight supported by the frame: 200 kg.

### Installation

