

Technical data sheet

VISIO TUNNEL

200



OPTIONS

Support frame	
Black, 6mm	✓
Stainless steel, 6mm	✓
Window frame	
Black	✓
Stainless steel	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
AIR-System	
for room air independent installation	✓



200



Technical data sheet

VISIO TUNNEL

200



PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	235 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Eco Design	✓
EN Norm 6.4.23	EN 13229
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

One side has a lifting door, the other side is fixed. Both can be tilted for cleaning.

200



Technical data sheet

VISIO TUNNEL

200



SERVICES

Thermal output	
Nominal heat output	8.6 kW
Thermal output range min./max.	7.5-8.6 kW
Fuelwood requirement	2.5 ≈ kg/h
Energy efficiency	80 %
Triple values	
Exhaust gas mass flow	7.7 g/s
Exhaust temperature	256 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	24 mg/Nm ³
CO emission at 13 % O ₂	0.071 %
CO emission at 13 % O ₂	887 mg/Nm ³
CO ₂ concentration	9.3 %
OGC at 13 % O ₂	44 mg/Nm ³
NO _x at 13 % O ₂	99 mg/Nm ³

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1200 mm

All information is provided without guarantee. Sketches are not true to scale.

24.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



Technical data sheet

VISIO TUNNEL



CONVECTION AIR

Convection air above	min. 1050 cm ²
Convection air below	min. 525 cm ²

Note

Maximum weight supported by the frame: 200 kg.

Installation

